

IN THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

Claims 1-8 (canceled)

Claim 9 (currently amended): ~~The method of Claim 8 including the further steps of:~~
A method for stabilization of vertebrae adjacent an intervertebral space, such as during a spinal fusion procedure, the steps including:

inserting an elongate primary segment between the vertebrae;

inserting an elongate secondary segment between the vertebrae, with the secondary segment crossing the primary segment;

rotating at least one of the segments after at least one of said inserting steps;

configuring the primary segment to have a greater height between a top surface and a bottom surface than a width between side surfaces thereof;

configuring the secondary segment to have a greater height between a top surface and a bottom surface than a width between side surfaces thereof;

rotating the elongate primary segment about a long axis thereof after said primary segment inserting step; and

rotating the secondary segment about a long axis thereof after said secondary segment inserting step.

Claim 10 (currently amended): ~~The method of Claim 1 including the further step of~~
A method for stabilization of vertebrae adjacent an intervertebral space, such as during a spinal fusion procedure, the steps including:

inserting an elongate primary segment between the vertebrae;

inserting an elongate secondary segment between the vertebrae, with the secondary segment crossing the primary segment; and

expanding a height of at least one of the segments to increase a height of the

segment between a top surface and a bottom surface thereof.

Claim 11 (original): The method of Claim 10 wherein said expanding step includes the step of advancing a spreading element longitudinally through an interior of the segment to move the top surface of the segment away from the bottom surface of the segment.

Claim 12 (original): The method of Claim 11 including the further step of providing the spreading element in the form of a wedge and configuring the segment to include a longitudinal bore having a height which tapers over at least a portion thereof such that linear advancement of the wedge between a proximal end of the segment and a distal end of the segment causes the top surface of the segment to move away from the bottom surface of the segment.

Claims 13-15 (canceled)

Claim 16 (currently amended): ~~The method of Claim 15 including the further steps of:~~ A method for stabilization of vertebrae adjacent an intervertebral space, including the steps of:

providing an elongate primary segment having a distal end spaced from a proximal end;

inserting the primary segment between the vertebrae along a first pathway;

providing an elongate secondary segment having a proximal end spaced from a distal end;

inserting the secondary segment between the vertebrae along a second pathway to a location where the distal ends of the segments are spaced from each other and the proximal ends of the segments are spaced from each other;

orienting the second pathway crossing the first pathway;

orienting the first pathway substantially linearly and aligned with a first posterior incision in a patient, the first incision defining a first implantation site for the primary segment;

orienting the second pathway substantially linearly and aligned with a second posterior incision in the patent defining a second implantation site for the secondary segment;

configuring the primary segment to have a height between a top surface and a bottom surface greater than a width between side surfaces thereof;

orienting the primary segment with the side surfaces initially adjacent the vertebrae during said primary segment inserting step;

rotating the primary segment to bring the top surface and the bottom surface of the primary segment into contact with the vertebrae;

configuring the secondary segment to have a height between a top surface and a bottom surface greater than a width between side surfaces thereof;

orienting the secondary segment with the side surfaces initially adjacent the vertebrae during said secondary segment inserting step; and

rotating the secondary segment to bring the top surface and the bottom surface of the secondary segment into contact with the vertebrae.

Claim 17 (original): The method of Claim 16 including the further steps of:

expanding a height of the primary segment between the top surface and the bottom surface thereof; and

expanding a height of the secondary segment between the top surface of the bottom surface thereof.

Claim 18 (currently amended): The method of ~~Claim 17~~ Claim 16 including the further step of delivering fusion material into the intervertebral space.

Claim 19 (canceled)

Claim 20 (currently amended): ~~The method of Claim 19 including the further steps of:~~ A method for inserting an implant with a first elongate segment and a second elongate segment into a patient, with at least a portion of the second segment crossing the first segment, the implant inserting method including the steps of:

making a first incision at a first implantation site;

inserting the first elongate segment through the first incision and along a first pathway to an implantation site within the patient;

making a second incision at a location spaced from the first incision;

inserting the second elongate segment through the second incision and along a second pathway to the implantation site;

configuring the first segment to have a height between a top surface and a bottom surface greater than a width between adjacent side surfaces;

orienting the first segment with the side surfaces facing away from the second pathway during said first segment inserting step;

rotating the first segment to cause at least one of the side surfaces to face the second pathway;

configuring the second segment to have a height between a top surface and a bottom surface greater than a width between side surfaces thereof;

orienting the second segment with the side surfaces facing away from the first pathway during said second segment inserting step; and

rotating the second segment to cause at least one of the side surfaces to face the first pathway.